

# Aimpoint®

## MICRO T-1™

No matter what your mission, the size and weight of your equipment is a critical factor. With the Aimpoint Micro T-1™, Aimpoint has introduced an aiming system that provides the performance of our full-sized sights in the smallest package possible.



Built to offer the same battle proven ruggedness as other Aimpoint products, the Micro T-1™ is able to perform under extreme conditions while adding negligible weight to your weapon. Suitable for use on Rifles, Carbines, Shotguns, Sub Machineguns and Handguns, the Aimpoint Micro T-1 is ideal as a stand-alone sight, and because it weighs less than 4 ounces including the integrated Picatinny mount, it can easily be “piggybacked” on top of larger magnifying scopes, night vision, or thermal imaging optics.

The performance of the Micro T-1 is optimized for use with all generations of night vision devices (NVDs), but is especially suited for 3rd generation night vision technology. Aimpoint’s unique band-pass coating on the front lens gives the highest possible dot brightness, while providing the clearest, brightest image possible when used with a 3rd generation NVD. With 4 NVD-compatible brightness settings and 8 day-light settings including one extra-bright setting, the Micro T-1 is ready for use around-the-clock.



**THE FUTURE IN SIGHT.**



**APPLICATION AREAS**

Law Enforcement	Primary use
Armed Forces - Special Units	Primary use
Hunters	Secondary use
IPSC Shooters	Secondary use

**APPLICATION FIREARMS**

Pistol - Revolver	Primary use
Bow	Secondary use
Magnum handgun	Secondary use
Semi-automatic rifle	Secondary use
Rifle with standard length action	Secondary use
Rifle with shorter action	Secondary use
Scout rifle	Secondary use
Shotgun	Secondary use
Carbine	Primary use

**TECHNOLOGY**

ACET	Advanced Circuit Efficiency Technology
------	--

**OPTICAL DATA**

Reflex collimator sight	Red dot sight
LED (Light Emitting Diode)	Totally eye-safe
Red dot size	4 MOA*
Parallax-free	No centering required
Eye relief	Unlimited
Anti-reflex coating & multilayer coating	All surfaces
Band Pass coating	For NVD compatibility
Magnification	1X

**ELECTRONIC DATA**

Battery	One 3V Lithium battery, type CR2032
Battery life	50,000 hours
Battery life, in hours, NVD position**	500,000 hours
Switch	Manual rotary switch
NVD and daylight settings	4 NVD & 8 daylight of which one extra bright

**MECHANICAL DATA**

Material housing	Extruded high strength aluminum
Surface finish	Anodized, semi-matte
Color	Black
Material lens covers	Rubber, black, matte
Adjustment	1 click = 13 mm at 100 meters = 1/2" at 100 yards
Mounting solution	Integrated Picatinny/Weaver

**ENVIRONMENTAL DATA**

Temperature range	-50° – +160° F, -45° – +71° C
Water resistance	Submersible to 25 m, 80 ft
Radioactive components used	None

**DIMENSIONS**

Length	62 mm, 2,4"
Width/height - sight only	41x36 mm, 1,6" x 1,4"
Width/height - including mount	62x41 mm, 2,4" x 1,6"
Weight - sight only	84 g, 3.0 oz
Weight sight with integrated mount	105 g, 3.7 oz

**ARTICLE NUMBER**

4 MOA	11830
-------	-------



**Unique features of the Micro T-1™**

- Ideal for rifles, carbines, shotguns, sub-machineguns and handguns.
- 1X (non-magnifying) parallax free optic.
- Compatible with all generations of Night Vision Devices (NVD).
- 4 night vision compatible settings and 8 daylight settings – one extra bright for use with laser protection glasses or in bright desert sunlight.
- Integral Picatinny-style mount allows easy attachment to any rail.
- Patent pending mount is keyed to the sight body to absorb recoil.
- New ACET technology allows 50,000 hours (over 5 years) of constant operation from one battery.
- 4 MOA dot.
- Hard anodized non-reflective finish.
- Submersible to 80 feet (25 meters).
- Precision adjustments for windage and elevation. Top of protective caps fits into holes on adjustment screws – no other tool required.
- Use as a stand alone sight or “piggybacked” on larger magnifying, thermal, or night vision optics.

\* MOA (minute of angle) 1 MOA = 30 mm at 100 meters = 1" at 100 yards  
 \*\* At room temperature

MO0807